

CCSDS Architecture Working Group

Architectural Models of Space Networking

June 4, 2003

Peter Shames

Mgr, JPL Information Systems Standards Program

+1.818.354.5740

peter.shames@jpl.nasa.gov




AGENDA

- Overview and Drivers
- Architectural Viewpoints
- ◆ Example Reference Architecture (RASDS) Views
- Application of RASDS to Space Internetworking
- Next Steps



NASA DATA SYSTEM STANDARDS PROGRAM A Physical View of a Space Data System





NASA DATA SYSTEM STANDARDS PROGRAM Space Mission Drivers

- INCREASED SPACE SEGMENT CAPBILITIES
 - * More miniaturization, more missions, more bang for the buck
 - * Higher date rates, more powerful onboard processing
 - Constellations and Formation Flying
 - Inter Spacecraft Communications
 - Positioning Relative to Each Other
 - * Autonomous Exploration
 - **♦** Less reliance on "Joystick Operations."
 - ◆ Dynamic Response to Environment (Precision EDL, Rendezvous & Docking)
 - * Highly networked
 - ♦ Re-configurable web of orbiting and landed sensors for in-situ, long-term and detailed observation, prediction and analysis.

Page: PMBS - 4

June 4, 2003

◆ HIGHLY DISTRIBUTED MULTI-ORGANIZATION DESIGN AND OPERATIONS TEAMS




Space Data System

Several Architectural Viewpoints



Business Concerns Organizational perspective



Connectivity

Physical Concerns
Node & Link perspective

Functional

Computational Concerns Functional composition

Information

Data Concerns Relationships and transformations

Communications

Protocol Concerns Communications stack perspective

Third Space Internet Workshop NASA/GRC


Architectural Models
Space Networking

Page: PMBS - 5 June 4, 2003

Derived from: RM-ODP



NASA DATA SYSTEM STANDARDS PROGRAM • Enterprise View





NASA DATA SYSTEM STANDARDS PROGRAM Unified Object Representation



Management Interfaces:

How objects are configured controlled, and reported upon



Service Interfaces:

How services are requested & supplied



Core Functions

What the object does



External Interfaces:


How external elements are controlled

Concerns:

Issues


Resources

Policies



• NASA DATA SYSTEM STANDARDS PROGRAM • Functional View


Example Functional Objects & Interactions





• NASA DATA SYSTEM STANDARDS PROGRAM • Connectivity View - Component Level


Nodes & Links







Connectivity + Functional Views

Mapping Functions to Nodes





CCSDS Space Communications Standards






NASA DATA SYSTEM STANDARDS PROGRAM Application of RASDS to Space Internetworking

- Only a single Functional View example is shown, many are possible
- Types of Space Links
- Connectivity Issues
- Communications Views
 - Near Earth
 - Deep Space
 - Proximity
- Other Considerations

Connector Properties: Types of Space Links



Source: A. Hooke, NASA/JPL



NASA DATA SYSTEM STANDARDS PROGRAM Connectivity Issues

Near Earth

- Internet protocol suite will work, modulo short pass times, link (re-)establishment, and modest RTLT issues
- SCPS protocols (w/ NGSI extensions) recommended solution

Proximity / In-Situ

- Internet protocol suite may work, modulo short pass times, link (re-)establishment, and the usual resource issues
- * Resource constraints on landed assets may preclude use of higher level protocols than simple link like Prox-1


Deep Space

- * Internet protocol suite *will not* work, almost every assumption in protocol suite design is violated by physics of environment
- * Possible to transport data between separate Internet-like domains using long haul protocols or new DTN / IPN approach

Communications View Composition


(Space Packet Transfer w/ SLE) GROUND **FLIGHT Payload SYSTEM SYSTEM** Command Commar Command Execution Generation C&DH **Space Space Packe Space** Packet (Relay **Packet Packet DSN** TC Space **TC Space** TC Space Onboard Onboard **Data Link** Data Link (Relay) Data Link Data Link Data Link Frame SLE SLE **CLTU CLTU** TCP/ TCP/ IP IP RF Onboard Onboard **RF** Seneration Physical **Physical PPP PPP** Generation Wavefor

Communications View Composition




Communications View Composition

(Deep Space Packet Transfer)




Communications View Composition





Communications View Composition

(Proximity, S/C to S/C or in Situ)






NASA DATA SYSTEM STANDARDS PROGRAM Other Considerations

- Emergency Commanding
 - * How to support this in an Internet environment?
- Security Concerns
 - Maintain Spacecraft Health & Safety
 - Prevent Denial of Service attacks
- Intermittent Connectivity
 - Most standard Internet protocols fail
 - * Where do you put recovery mechanisms?
- Installed Base
 - Major multi-agency investment in hardware and software
 - Proven and agreed means to provide interoperability and cross support
 - * Commercial suppliers have many space qualified products



NASA DATA SYSTEM STANDARDS PROGRAM Next Steps

- Identify solid mission requirements
 - What are real documented drivers for change?
 - * Where are these new techniques appropriate and where do they not work?
- Identify agreed NASA infusion path
 - Work with existing NASA and international space agency supported standards organization, CCSDS
 - Identify ways to evolve existing base to include new capabilities and preserve existing capabilities and functionality
 - Apply Internet technologies only where they make technical and economic sense



NASA DATA SYSTEM STANDARDS PROGRAM Acknowledgements

- ◆ The RASDS was designed as part of the program of work of Consultative Committee for Space Data Systems (CCSDS).
- ◆ It was performed by the Architecture Working group (AWG), chaired by Takahiro Yamada, ISAS
- Other AWG members who actively participated are listed below:
 - Fred Brosi, NASA/GST
 - Dan Crichton, NASA/JPL
 - Adrian Hooke, NASA/JPL
 - Steve Hughes, NASA/JPL
 - Niklas Lindman, ESA/ESOC

- Nestor Peccia, ESA/ESOC
- Lou Reich, NASA/CSC
- Don Sawyer, NASA/GSFC
- Peter Shames, NASA/JPL
- Anthony Walsh, ESA/Vega




BACKUP SLIDES

• NASA DATA SYSTEM STANDARDS PROGRAM • Rationale

(or, Why do space agencies need standards?)

- **♦**Cross-support
 - * Ground assets (e.g. DSN)
 - Space assets (e.g. Mars relay)
- ◆ Interoperability
 - Multi-agency support agreements
 - * Multi-mission support arrangements
- ◆Reduce costs
 - * Shared (expensive, scarce) resources
 - ❖ S/W and H/W reuse
 - ***** Commercial implementations
- ◆Increase reliability / reduce risks
 - * Through use of well tested local and commercial implementations




NASA DATA SYSTEM STANDARDS PROGRAM Reference Architecture

Purpose

- Establish an overall CCSDS approach to architecting and to developing domain specific architectures
- ◆ Define common language and representation so that challenges, requirements, and solutions in the area of space data systems can be readily communicated
- Provide a kit of architect's tools that domain experts will use to construct many different complex space system architectures
- Facilitate development of standards in a consistent way so that any standard can be used with other appropriate standards in a system
- Present the standards developed by CCSDS in a systematic way so that their functionality, applicability, and interoperability may be clearly understood




• NASA DATA SYSTEM STANDARDS PROGRAM • Enterprise View (Enterprise Objects)





• NASA DATA SYSTEM STANDARDS PROGRAM • Connectivity View (Nodes and Links)






Functional View (Functional Objects)




Connectivity+Functional View (Nodes, Links and Functional Objects)






Information View (Information Objects)




Functional+Information View (Functional Objects and Information Objects)





Connectivity+Functional+Communication View (Nodes, Links,

Functional Objects and Communications Objects)





NASA DATA SYSTEM STANDARDS PROGRAM Space Data System


Architectural Notation



Object




Object with Interface




Object Encapsulation



Node (physical location)



Node Encapsulation (physical aggregation)




Concerns

Logical Link


Physical Link

Space Link (rf or optical)



• NASA DATA SYSTEM STANDARDS PROGRAM • Enterprise View


Single Agency Mission Domain & Enterprise Objects
Operations Planning Phase





NASA DATA SYSTEM STANDARDS PROGRAM Connectivity View - High Level


Single Agency Mission Domain & Nodes






NASA DATA SYSTEM STANDARDS PROGRAM Information Object

Basic Relationships





Communications View

